

# Package: DensParcorr (via r-universe)

September 13, 2024

**Type** Package

**Title** Dens-Based Method for Partial Correlation Estimation in Large Scale Brain Networks

**Version** 1.1

**Date** 2018-09-19

**Author** Yikai Wang, Jian Kang, Phebe Brenne Kemmer and Ying Guo

**Maintainer** Yikai Wang <johnzon.wyk@gmail.com>

**Depends** R (>= 3.1.0), clime, gplots

**Description** Provide a Dens-based method for estimating functional connection in large scale brain networks using partial correlation.

**License** GPL-2

**NeedsCompilation** no

**Date/Publication** 2018-09-20 17:10:25 UTC

**Repository** <https://johnzonwyk.r-universe.dev>

**RemoteUrl** <https://github.com/cran/DensParcorr>

**RemoteRef** HEAD

**RemoteSha** 3f658a70f16f8f002adda8437c71b21f9bdee135

## Contents

DensParcorr . . . . .	2
prec2dens . . . . .	4
prec2part . . . . .	5

<b>Index</b>	<b>6</b>
--------------	----------

---

DensParcorr

*Conduct the Dens-Based approach for partial correlation estimation*


---

### Description

This function is to conduct the *Dens*-based approach for partial correlation estimation in large scale brain network study.

DensParcorr is the main function in this package. prec2dens and prec2part are sub-functions called by DensParcorr.

### Usage

```
DensParcorr(data,select=FALSE,dens.level="plateau",plateau.thresh=0.01,
            Parcorr.est=NULL,directory=NULL,lambda=NULL)
```

### Arguments

data	Input data matrix with dimension of T×M where T is the number of observations and M is the number of nodes. For example, in fMRI data the T is the number of scans.
select	Whether to conduct the <i>Dens</i> -based selection. If FALSE, output will only contain the estimated partial correlation list and precision matrix list corresponding to the default tuning parameter series ranging from 1e-8 to 0.6. If TRUE, the output will include the previous results and the selected partial correlation matrix and precision matrix corresponding to the specified density level. Default is FALSE.
dens.level	Specify the density level in <i>Dens</i> -based tuning parameter selection method, including the plateau based density selection (dens.level = "plateau") and p percentage density selection (dens.level = p, 0<p<1). This option is valid only when select=TRUE. See Details. Default is "plateau".
plateau.thresh	The criterion to select the plateau. This option is valid only when select=TRUE. See Details. Default value is 0.01.
Parcorr.est	Previous output from DensParcorr function.
directory	The directory to output the figures and precision matrices and the partial correlation matrices. The default (directory=NULL) is to output in the current working directory.
lambda	The lambda value for estimating the precision matrix ranging from 0 to 1. The default is NULL. If specified, no extra <i>Dens</i> -based step will be conducted.

### Details

This function implements the statistical method proposed in Wang et al. (2016) to estimate partial correlation matrix for studying direct connectivity in large-scale brain network. The method derives partial correlation based on the precision matrix estimated via Constrained L1-minimization Approach (CLIME) (Cai et al., 2011). This function applies the *Dens*-based tuning parameter selection method in Wang et al. (2016) to help select an appropriate tuning parameter for sparsity

control in the network estimation. Below is the brief step of *Dens*-based approach.

First, we specify a series of tuning parameters  $\{\lambda_n\}$ . Then, based on  $\{\lambda_n\}$  we estimate a list of precision matrices  $\Omega(\lambda_n)$  and evaluate the density level of each precision matrix based on the *Dens* criterion function in equation (5) of Wang et al. (2016). This will provide the users the profile of the density level corresponding to the series of tuning parameters in  $\{\lambda_n\}$ . Users can use the `dens.level` option to specify the desired density level in the precision matrix estimation. If `dens.level="plateau"`, the function will select the plateau point  $\lambda_{plateau}$  in the density profile based on the `plateau.thresh` and output the precision matrix  $\Omega(\lambda_{plateau})$ . If `dens.level=p` and  $0 < p < 1$ , the function will select the tuning parameter  $\lambda_p$  to achieve  $p$  percentage density and output the precision matrix  $\Omega(\lambda_p)$ . Then, the partial correlation matrix will be derived from the precision matrix. Further details can be found in the Reference.

The density profile and the heatmaps of precision matrices and partial correlation matrices will be saved in `directory`, and the estimated list of precision matrices and partial correlation matrices will also be saved in `directory`.

When users would like to run the function multiple times on the same input data for different `dens.level`, it is computationally more efficient to read in the previous output from `DensParcorr` to `Parcorr.est` so that the function won't need to re-estimate the partial correlations based on the previous tuning parameters.

## Value

An R list from `DensParcorr` containing the following terms:

<code>selected.partial.corr</code>	Selected Partial Correlation matrix corresponding to <code>dens.level</code> . Only when <code>select=TRUE</code> .
<code>selected.precision</code>	Selected Precision matrix corresponding to <code>dens.level</code> . Only when <code>select=TRUE</code> .
<code>selected.lambda</code>	Selected tuning parameter corresponding to <code>dens.level</code> . Only when <code>select=TRUE</code> .
<code>lambda.list</code>	The series of tuning parameters used for estimation and density profile.
<code>partial.corr.list</code>	Estimated Partial Correlation matrix list corresponding to <code>lambda.list</code> .
<code>precision.list</code>	Estimated Precision matrix list corresponding to <code>lambda.list</code> .
<code>Dens</code>	Actual density levels for estimated precision matrix list.
<code>Dens.Percentage</code>	Actual percentage density levels for estimated precision matrix list.
<code>selection.method</code>	The method used for tuning parameter selection. For percentage <i>Dens</i> selection, this value will include the actual <i>Dens</i> percentage and the nominal <i>Dens</i> percentage. Only when <code>select=TRUE</code> .

**Author(s)**

Yikai Wang, Jian Kang, Phebe Brenne Kemmer and Ying Guo  
 Maintainer: Yikai Wang <yikai.wang@emory.edu>

**References**

Wang, Y., Kang, J., Kemmer P. and Guo, Y. (2016). *An efficient and reliable statistical method for estimating functional connectivity in large scale brain networks using partial correlation*. Front. Neurosci. 10:123. doi: 10.3389/fnins.2016.00123

Cai, T.T., Liu, W., and Luo, X. (2011). *A constrained  $\ell_1$  minimization approach for sparse precision matrix estimation*. Journal of the American Statistical Association 106(494): 594-607.

**Examples**

```
# require(gplots)
# require(clime)

## Simulated the data to use.
# data = matrix(rnorm(200),ncol=20)

##### Example 1: Estimate the partial correlation matrices for the
##### default series of tuning parameters.
# t0 = proc.time()[3]
# dens.est = DensParcorr(data,select=FALSE)
# proc.time()[3]-t0

##### Example 2: Estimate the network that reaches 40% density level.
# partial.dens.est = DensParcorr(data,dens.level =.4,select=TRUE)

##### Example 3: Now, estimate the 60% density level network based
##### on the same data. To speed up computation, we read in the
##### previous output from Example 2 into Parcorr.est
# t0 = proc.time()[3]
# partial.dens.est2 = DensParcorr(data, Parcorr.est = partial.dens.est,
#                               dens.level=.6,select=TRUE)
# proc.time()[3]-t0
```

---

```
prec2dens
```

---

*Calculate Dens value from Precision Matrix*

---

**Description**

This function evaluates the density level of a precision matrix based on the Dens criterion function in equation (5) of Wang et al. (2016).

**Usage**

```
prec2dens(precision)
```

**Arguments**

precision      Input precision matrix (symmetric and positive definite).

**Value**

Density level from Precision matrix.

**Author(s)**

Yikai Wang, Jian Kang, Phebe Brenne Kemmer and Ying Guo  
Maintainer: Yikai Wang <yikai.wang@emory.edu>

**References**

Wang, Y., Kang, J., Kemmer P. and Guo, Y. (2016). *An efficient and reliable statistical method for estimating functional connectivity in large scale brain networks using partial correlation.* Front. Neurosci. 10:123. doi: 10.3389/fnins.2016.00123

---

prec2part

*Calculate Partial Correlation Matrix from Precision Matrix*

---

**Description**

This function is to derive the partial correlation matrix from the precision matrix.

**Usage**

```
prec2part(Precision)
```

**Arguments**

Precision      Input precision matrix (symmetric and positive definite).

**Value**

Calculated partial correlation matrix.

**Author(s)**

Yikai Wang, Jian Kang, Phebe Brenne Kemmer and Ying Guo  
Maintainer: Yikai Wang <yikai.wang@emory.edu>

**References**

Wang, Y., Kang, J., Kemmer P. and Guo, Y. (2016). *An efficient and reliable statistical method for estimating functional connectivity in large scale brain networks using partial correlation.* Front. Neurosci. 10:123. doi: 10.3389/fnins.2016.00123

# Index

DensParcorr, [2](#)

prec2dens, [4](#)

prec2part, [5](#)